

COLUMBIAHALLE

VENUE SPECS

/print version

venue production manager: Roger Hass
Thorsten Mansfeld

contact: roger@cumbiahalle.berlin
thorsten@cumbiahalle.berlin

fon/fax: 0049 (0) 30 / 61 65 45 18
0049 (0) 30 / 61 65 45 17

adress: Columbiashalle
Gastro- und Betriebs GmbH
Columbiadamm 13-21
10965 Berlin



technical data

size:	1150 qm main hall 410 qm gallery
capacity:	3500 terraces 1400 seats
parking:	3 Trucks 3 Nightliner 3 Vans
backstage:	2 big production offices 1 small production office 2 big dressing rooms (je 16,5 qm) 2 small dressing rooms (je 9,0 qm) 1 star dressing room (incl. toilett, shower, mirrors, 2 fridges, couch, chairs, TV, privat garden, darts)
toilets:	4 (Backstage)
shower:	2 double showers 2 single showers
catering:	20 Pax
kitchen:	1 gas stove (5 flame, electric oven) 3 large fridges 1 gastro sink worksurfaces
internet:	50.000 kbit/s, WLAN



produktionsoffice 1: Tel. 0049 (0) 30 / 61 65 45 11
Tel. 0049 (0) 30 / 61 65 45 12

produktionsoffice 2: Tel. 0049 (0) 30 / 61 65 45 13
Tel. 0049 (0) 30 / 61 65 45 14

stage: 15,00 m x 9,00 m (basic stage)
height 1,40 m
15,00 m x 10,00 m to increase (charged extra)
15,00 m x 8,00 m (full seating)

headroom - stage to support 6,60 m
headroom - hall floor to support 8,00 m

loading: ground level 10,00 m

loading doors: 1 back stage
height 3,35 m, width 2,95 m

2 back stage
height 2,20 m, width 2,90 m

3 front of the hall area
height 2,05 m, width 2,90 m

rigging: There are two light beams at 9,00 m distance from each other over the stage and pull up to the gallery.

The carrier points are 500 kg per 3,00 m with a load. There two sound beams each 6,60 m long and 14,00 m distance from each other left and right over the stage. The carrier points with a weight of 700 kg in the middle of beam include motors and cradle! Upstage od downstage 350 kg load.



rigging height: beam height 6,60 m (from stage)
beam height 8,00 m (from ground)

motors rigging: There are 6 house motors in the rig. If there are used it costs per the motor 25,00 EUR net.

4 motors D8 Plus
2 motors D8 (sound must be saved)

electricity (lights): stage right
max. 400 Amp

1x Powerlock 400 Amp 3 Phasen PE+N
2x 125 Amp CEE 3 Phasen (red)
2x 63 Amp CEE 3 Phasen (red)
2x 32 Amp CEE 3 Phasen (red)
2x 16 Amp CEE 3 Phasen (red)
4x 16 Amp single Phase (blue)
4x 16 Amp Schuko

1x max 250 Amp for open ends

electricity (sound):stage left
max. 250 Amp

1x Powerlock 250 Amp 3 Phasen PE+N
1x 125 Amp CEE 3 Phasen (red)
2x 63 Amp CEE 3 Phasen (red)
2x 32 Amp CEE 3 Phasen (red)
2x 16 Amp CEE 3 Phasen (red)
4x 16 Amp single Phase (blue)
4x 16 Amp Schuko

1x max 250 Amp for open ends



spotpower (gallery):

2x 16 Amp CEE (red)
6x 16 Amp Schuko

loading area: 2 trucks

The back of the trucks need to be about
2,00 m inside the loadings docks.
Truck motors should just be operated to
move the vehicles!

Merch fee: 300,00EUR plus 19% tax
tables are available



extras

delay-line:

The Columbiahalle has a fixed delay line consisting of:

4x VUE Audiotechnik a-15
in Bi-Amp Mode

VUE Audiotechnik V4-Engine
Has stereo input in analog balanced XLR or
AES / EBU digital XLR and a network port

The speakers are about 4,00 m behind the balcony railing and provide the rearmost lower balcony area with direct sound to compensate for acoustic shadowing in suspended main facilities.

The delay settings should be on the amount of suspended main system and the depth of the stage placed at about 19,5 m dependent.

Normally the terminal of a computer is not required. The amplifier is connected via two speakon cable with a junction box in the area of FOH place.

The venue production manager stands ready with Amp in case inclusive of network and speakon cable.

Delay line using is free!